

02



# ELECTRICAL DISTRIBUTION

# PLASTIC DISTRIBUTION BOARDS GREY DOOR



## MAIN TECHNICAL FEATURES

- Resistance: Chemical agents, alkali, oils, salts, etc.
- Rated Voltage: Up to 690V
- Maximum Current: Up to 800A
- Operating Temperature: -35°C + 65°C
- Material: HB ABS Halogen Free
- Mounting Plate: Galvanised steel 1mm
- IP Degree: IP65
- IK Degree: IK08
- Colour: RAL7035 Grey (Other colours on request)
- **CE** RoHS



HALOGEN  
FREE

 IP65

**CE**

## PLASTIC DISTRIBUTION BOARDS - GREY DOOR

CODE	L (mm)	W (mm)	H (mm)	WEIGHT(kg)
PP3001	200	300	130	1.80
PP3002	250	350	150	2.40
PP3004	300	400	170	3.00
PP3005	300	400	220	3.40
PP3006	350	500	190	4.35
PP3003	400	500	175	4.50
PP3007	400	500	240	5.40
PP3008	400	600	200	5.85
PP3010	500	700	250	9.70
PP3021	600	800	260	10.80

# PLASTIC DISTRIBUTION BOARDS TRANSPARENT DOOR



## MAIN TECHNICAL FEATURES

- Resistance: Chemical agents, alkali, oils, salts, etc.
- Rated Voltage: Up to 690V
- Maximum Current: Up to 800A
- Operating Temperature: -35°C + 65°C
- Material: HB ABS Halogen Free + Polycarbonate (Doors)
- Mounting Plate: Galvanised steel 1mm
- IP Degree: IP65
- IK Degree: IK08
- Colour: RAL7035 Grey body, transparent door (Other colours on request)
- **CE** RoHS



HALOGEN  
FREE

IP65

**CE**

## PLASTIC DISTRIBUTION BOARDS - TRANSPARENT DOOR

CODE	L (mm)	W (mm)	H (mm)	WEIGHT(kg)
PP3011	200	300	130	1.80
PP3012	250	350	150	2.40
PP3014	300	400	170	3.00
PP3015	300	400	220	3.40
PP3016	350	500	190	4.35
PP3013	400	500	175	4.50
PP3017	400	500	240	5.40
PP3018	400	600	200	5.85
PP3020	500	700	250	9.70
PP3022	600	800	260	10.80

# MODULAR DISTRIBUTION BOARDS GREY DOOR



## MAIN TECHNICAL FEATURES

- Resistance: Chemical agents, alkali, oils, salts, etc.
- Rated Voltage: Up to 690V
- Maximum Current: Up to 800A
- Operating Temperature: -35°C + 65°C
- Material: HB ABS Halogen Free
- IP Degree: IP65
- IK Degree: IK08
- Colour: RAL7035 Grey (Other colours on request)
- **CE** RoHS



HALOGEN  
FREE




## MODULAR DISTRIBUTION BOARDS - GREY DOOR

CODE	L (mm)	W (mm)	H (mm)	MCB Qty	WEIGHT(kg)
PP3102	250	350	150	18 (9x2)	2.50
PP3104	300	400	170	24 (12x2)	3.40
PP3106	350	500	190	45 (15x3)	4.50
PP3108	400	600	200	60 (15x4)	6.00

# MODULAR DISTRIBUTION BOARDS TRANSPARENT DOOR



## MAIN TECHNICAL FEATURES

- Resistance: Chemical agents, alkali, oils, salts, etc.
- Rated Voltage: Up to 690V
- Maximum Current: Up to 800A
- Operating Temperature: -35°C + 65°C
- Material: HB ABS Halogen Free + Polycarbonate (Doors)
- IP Degree: IP65
- IK Degree: IK08
- Colour: RAL7035 Grey body, transparent door (Other colours on request)
-  RoHS



HALOGEN  
FREE



## MODULAR DISTRIBUTION BOARDS - TRANSPARENT DOOR

CODE	L (mm)	W (mm)	H (mm)	MCB Qty	WEIGHT(kg)
PP3112	250	350	150	18 (9x2)	2.50
PP3114	300	400	170	24 (12x2)	3.40
PP3116	350	500	190	45 (15x3)	4.50
PP3118	400	600	200	60 (15x4)	6.00